

Die Wandtresore BULDOK sind zur Aufbewahrung von Schmuckstücken, Geldern, Wertpapieren, wichtigen Dokumenten, event. weiteren Wertgegenständen bestimmt. Die Konstruktionslösung ermöglicht deren Einbau in starke Umfangsmauern.

Die Tresortüren werden aus Stahlblech, 12 mm dick (Typ 41.0, 42.0 – 8 mm) hergestellt und sind in den Rahmen, Stärke 14 mm (Typ 41.0, 42.0 – 10 mm) eingesetzt. Die Türen sind mit Hilfe eines Spezialmechanismus an drei Seiten abgesperrt (außer Typ 41.0, 42.0, 41.1, 42.1). Die vierte Türseite ist durch Festhaken gesichert. Dadurch wird eine vollständige Sicherung gegen Aufbrechen erreicht.

Die Betätigung des Mechanismus erfolgt mit dem Tresorschmetterlingsschloß – bei den Tresortypen 42 mit Kodeschloß SARGENT & GREENLEAF, ergänzt mit der Möglichkeit der Einstellung von fast einer Million Nummerkombinationen. Die Schlösser sind ebenfalls gegen Aufbohren geschützt.

Im Inneren des Tresors befindet sich eine herausnehmbare Trennwand und bei den Typen 41.31 und 41.41 (event. 42.31, 42.41) ein weiterer absperrbarer Schrank.

Alle typen von Tresoren werden in zwei farbtönen geliefert.

Die Tresore weisen eine Brandfestigkeit auf, die durch Prüfung der Feuerbeständigkeit nach ČSN 91 1268 durch die Feuerattest- und Bauentwicklungsanstalt i Prag beglaubigt wurde. Für die Sicherung der Leistungen von der Versicherungsanstalt (feststellen des Limitbetrages) gelten die von der zuständigen Versicherungsanstalt herausgegebenen Versicherungsbedingungen.



The wall safes Buldok are intended to store jewels, money, certificates, important documents, eventually other valuable items. The design allows for the safes to be inserted in strong outside walls.

The door of the safe is of steel plate 12 mm thick (8 mm in Type 41.0 and 42.0) and is fitted into a frame 14 mm thick (10 mm in Types 41.0 and 42.0). The door closes on three sides into the frame by means of a special mechanism. The fourth side is secured by a fixed hinge. This arrangement achieves perfect proofing against break-in.

The mechanism is controlled by a "butterfly" lock supplemented in models 42 by a coded lock SARGENT & GREENLEAF with one million of numerical combinations. The locks are also provided with protection against drilling.

A removable partition, and in models 41.31, 41.41, 42.31, and 42.41 an additional lockable box are located within the safe.

All types of safes are delivered in two colour variants.

The safety level has been certified by The Crime Prevention Institute Prague.

The safes indicate resistance against fire as certified by tests to Czech National Standard 91 1268 performed by the Construction Fire Testing Research Institute in Prague.

For insurance coverage and the determination of the limit amount consult applicable insurance policies.



42-0



41-31



42-2

Typ Type	Vnější rozměry v×š×h (mm) Außenabmessungen H×B×T (mm) Outside dimensions h×w×d (mm)	Vnitřní rozměry v×š×h (mm) Innenabmessungen H×B×T (mm) Inside dimensions h×w×d (mm)	Objem (litru) Volumen (Liters) Volume (liters)	Hmotnost (kg) Gewicht (kg) Weight (kg)
41.0 / 42.0	280 × 210 × 150	230 × 160 × 100	3,7	10
41.1 / 42.1	270 × 340 × 238	220 × 290 × 175	11	17,5
41.2 / 42.2	270 × 540 × 290	220 × 490 × 230	25	29
41.31 42.31	430 × 450 × 290	380 × 400 × 230 vnitřní schránka / Innenbehälter / inside box 185 × 295 × 90	35	37
41.41 42.41	630 × 450 × 330	580 × 400 × 270 vnitřní schránka / Innenbehälter / inside box 115 × 400 × 130	62	51



KOVOPLAST CHLUMEC NAD CIDINOU, a. s.
ul. Kozelkova 131/IV, 503 51 Chlumeck nad Cidlinou
Tel.: 495 484 543, Fax: 495 485 230

www.kovoplast.cz
E-mail: kovoplast@kovoplast.cz